



Output voltage programming options	
A. Internal potentiometer	B. External voltage
<p>Red +4.75V to +6V 8mA typical</p> <p>Black 0V</p> <p>Yellow 0V</p> <p>White Monitor</p>	<p>Red +4.75V to +6V 8mA typical</p> <p>Black 0V</p> <p>Yellow nc</p> <p>White Control 0 to +1.8V Monitor</p>
nc: no connection - isolated lead	
Monitor: 1/1000 of voltage applied to photomultiplier anode (a)	

Sales Drawing

 Bury Street, Ruislip, HA4 7TA, UK	Issue	Date	C/Note No.	Sign	Material	Drawn by M. Stoodley	Project
	1	05.03.09				Date 6 January 2010	P25P-09
Limits on all dimensions unless otherwise stated Linear dimensions $\pm 0.1\text{mm}$ Angular dimensions $\pm 0.1^\circ$	2	14.01.10	S00266		Finish	Scale 1:1	Title
					Surface finish Unless otherwise specified	Checked M. Stoodley	Photodetector package
Confidentiality Notice . This document (including all information contained therein) is owned by Sens-Tech Limited and must be kept in confidence and used solely for the owner's specified purposes. This document must not be copied or reproduced, nor divulged, in whole or part, without the owner's prior written consent.	THIRD ANGLE PROJECTION				Approved A. Sellars	Drawing Number	
					Sheet size A3 F/DO007 issue 1	25894 G 2326	Sheet 1 of 1