



Programming options for integral high voltage power supply	
A. Internal potentiometer (access from end face of package)	B. External voltage
NC: no connection - isolated lead	
Monitor: 1/1000 of voltage applied to photomultiplier	

- Notes**
1. Case is internally connected to 0V.
 2. Case finish, Black powder coat paint.
 3. Typical input current 65mA at 5V.

Sales Drawing

 Bury Street, Ruislip, HA4 7TA, UK	Issue	Date	C/Note No.	Sign	Material	Drawn by M. Stoodley	Project
	1	11.01.10				Date 11 January 2010	P30PVN-31
Limits on all dimensions unless otherwise stated Linear dimensions $\pm 0.1\text{mm}$ Angular dimensions $\pm 0.1^\circ$					Finish	Scale 1:1	Title
					Surface finish Unless otherwise specified	Checked M. Stoodley	Photodetector package
Confidentiality Notice . This document (including all information contained therein) is owned by Sens-Tech Limited and must be kept in confidence and used solely for the owner's specified purposes. This document must not be copied or reproduced, nor divulged, in whole or part, without the owner's prior written consent.					THIRD ANGLE PROJECTION	Approved A. Sellars	Drawing Number
						Sheet size A3 F/DO007 issue 1	25894 G 2333 Sheet 1 of 1